

M8 Male Molded Cables, Angled
M8 Circular Connector

Download date : 2024-05-09



Connector Series : M8
Gender : Male
Coding : A, B
Locking Type : Fix Screw
Mounting Type: Angled
Part No : M08-X**-RA0-M02-BC*-XXX

X:A, B Coding
** : 03, 04, 05, 06, 08 (Pin)

ST0:0=Unshielded , 2=Full
Shield , 1=Ground
BC*:BCC=Cable Jacket PVC(For
Molded Cable)
BC*:BCR=Cable Jacket PUR(For
Molded Cable)

XXX:050=0.5M, 100=1M,
10M=10M...(Length)



For reference only!version1.0

Technical Data

Standard	IEC61076-2-104
Ambient Temperatur	-25°C~+80°C
Insulation Resistance	≥100MΩ
Contact Resistance	≤5mΩ
IP Class	IP67
Mating Endurance	>100 Mating Cycles


Material Data

Connector Carriers	PA
Connector Contacts	Copper Alloy With Gold Plated 铜镀金
Connector Nut/Screw	Copper Alloy With Nickel Plated 铜镀镍
Shielding	Shielded 屏蔽/Unshielded 非屏蔽
Connector Overmold	TPU

Electrical Data & Mechanical Date

Contacts Pin	3/4Pins	5Pins	8Pins
Rated Current	3A	3A	1.5A
Voltage AC/DC	50V/60V	30V/30V	30V/30V
Wire Range AWG/mm ²	24/0.25	24/0.25	26/0.14
Cable Jacket	PUR/PVC		

Dimensions



Specification Selection Table

M8 Male Molded Cables, Angled
M8 Circular Connector

Download date : 2024-05-09



Contacts Pin数	Available Coding 防插错编码	Rated Current 额定电流	Voltage 电压		Wire Range 接线范围		Cable Jacket 线缆外被	Part NO. 产品编号
			AC	DC	AWG	mm ²		
03Pins	 A-Coding	3A	50V	60V	24	0.25	PVC	M08-A03-RA*-M02-BCC-XXX
							PUR	M08-A03-RA*-M02-BCR-XXX
04Pins	 A-Coding	3A	50V	60V	24	0.25	PVC	M08-A04-RA*-M02-BCC-XXX
							PUR	M08-A04-RA*-M02-BCR-XXX
05Pins	 B-Coding	3A	30V	30V	24	0.25	PVC	M08-B05-RA*-M02-BCC-XXX
							PUR	M08-B05-RA*-M02-BCR-XXX
06Pins	 A-Coding	1.5A	30V	30V	26	0.14	PVC	M08-A06-RA*-M02-BCC-XXX
							PUR	M08-A06-RA*-M02-BCR-XXX
08Pins	 A-Coding	1.5A	30V	30V	26	0.14	PVC	M08-A08-RA*-M02-BCC-XXX
							PUR	M08-A08-RA*-M02-BCR-XXX