



Connector Series : M87=7/8"

Gender : Male

Coding : A

Locking Type : Fix Screw

Mounting Type: Rear Fastened

Part No : M87-A**-ST0-M01-BH_

A:A Coding

** : 02, 03, 04, 05Pin

BH_:3=3=PG13.5(OD3),4=PG11(OD4),5=M20x1.5(OD5)



For reference only!version1.0

Technical Data

Ambient Temperatur	-25℃-+85℃
Insulation Resistance	≥100MΩ
Contact Resistance	≤5mΩ
IP Class	IP67
Mating Endurance	>100 Mating Cycles

Material Data

Connector Carriers	PA
Connector Contacts	Copper Alloy With Gold Plated 铜镀金
Connector Nut/Screw	Copper Alloy With Nickel Plated 铜镀镍
Seal/O-Ring	FKM 氟橡胶

Shielding	Unshielded 非屏蔽			
-----------	----------------	--	--	--

Electrical Data & Mechanical Date

Contacts Pin	2Pins	3Pins	4Pins	5Pins
Rated Current	13A	13A	13A	8A
Voltage AC/DC	300V			
Contacts Termination	PCB Version			

Accessories

-



[7/8" Female Molded Cables, Straight](#)



[7/8" Female Molded Cables, Angled](#)



[7/8" T Type Male-Female Molded With Cable](#)



[7/8" T-Splitter, Male-Female-Female](#)