



PCB connector  
Rated current: 15 A  
Rated voltage: 300 V  
Pitch: 5.0 mm  
Mounting: Reflow soldering



For reference only!version1.0

UL/CUL

| Use Group                    | B     | C | D   |
|------------------------------|-------|---|-----|
| Rate Voltage [V]             | 300   | - | 300 |
| Rated Current [A]            | 15    | - | 10  |
| Wire Range [AWG]             | /     |   |     |
| Dielectric Voltage-Withstand | 1.6KV |   |     |

IEC

|                                               |     |     |     |
|-----------------------------------------------|-----|-----|-----|
| Overvoltage Category                          | III | III | II  |
| Contamination Class                           | 3   | 2   | 2   |
| Rated Voltage [V]                             | 250 | 320 | 400 |
| Rated Current [A]                             | 12  | 12  | 12  |
| Impulse withstand voltage [KV]                | 4   | 4   | 4   |
| Conductor cross section[solid/flexible] [mm²] | /   |     |     |

Material

|                     |     |
|---------------------|-----|
| Insulation Material | LCP |
|---------------------|-----|


|                              |              |
|------------------------------|--------------|
| Flame relardant rating       | UL94V-0      |
| Conductor Material           | Copper alloy |
| Plating of conductor surface | Sn plated    |

Other Data


|                            |              |
|----------------------------|--------------|
| Pitch/Poles [mm]/[P]       | 5.0/2*2-2*24 |
| Stripping Length [mm]      | /            |
| Screw/Torque(Max)[N.m]     | /            |
| Operating temperature [°C] | -40~+130     |
| Soldering temperature      | 285°C/10S    |
| Pin dimensions [mm]        | 1.0*1.0      |
| PCB Hole Diameter [mm]     | Ø1.7         |

Dimensions

PCB opening diagram



Accessories



[WJ2EDGKNG-5.0](#)