


WJ239R-7.5

弹簧式PCB接线端子

下载日期:2024-05-02



弹簧式PCB连接器

额定电流: 40 A

额定电压: 600 V

使用线径: 24-8 AWG

间距: 7.5 mm

安装: 波峰焊



目录仅供参考，实际规格依产品工程图为准 版本1.0

技术数据-UL/CUL

等级 Use Group	B	C	D
额定电压 Rate Voltage [V]	600	600	600
额定电流 Rated Current [A]	40	40	5
接线范围 Wire Range [AWG]	24~8		
耐电压 Dielectric Voltage-Withstand	2.2KV		

技术参数-IEC

过电压类别 Overvoltage Category	III	III	II
污染等级 Contamination Class	3	2	2
额定电压 Rated Voltage [V]	800	1000	1000
额定电流 Rated Current [A]	41	41	41
额定冲击电压 Impulse withstand voltage [KV]	8	8	6
导线截面积[硬/柔] Conductor cross section [mm²]	0.2~10	0.2~6	

材料 Material

WJ239R-7.5

弹簧式PCB接线端子

下载日期:2024-05-02



绝缘材料 Insulation Material	PA66
阻燃等级 Flame relardant rating	UL94V-0
导体材料 Conductor Material	Copper alloy
导体表面镀层 Plating of conductor surface	Sn plated

一般参数 Other Data

间距/极数 Pitch/Poles [mm]/[P]	7.5/2~18
剥线长度 Stripping Length [mm]	15
螺丝/扭矩 Screw/Torque(Max)[N.m]	/
工作温度 Operating temperature [°C]	-40~+105
焊锡温度 Soldering temperature	260°C/5S
引针尺寸 Pin dimensions [mm]	1.7*0.8
PCB板孔径 PCB Hole Diameter [mm]	□2.1

尺寸图

PCB开孔图

