


WJ2EDGB-5.0/5.08

插拔式接线端子

下载日期:2024-05-06



	插拔式连接器 额定电流: 15 A 额定电压: 300 V 间距: 5.0 mm/5.08 mm 安装: 波峰焊
---	---



目录仅供参考，实际规格依产品工程图为准 版本1.0

技术数据-UL/CUL

等级 Use Group	B	C	D
额定电压 Rate Voltage [V]	300	-	300
额定电流 Rated Current [A]	15	-	10
接线范围 Wire Range [AWG]	/		
耐电压 Dielectric Voltage-Withstand	1.6KV		

技术参数-IEC

过电压类别 Overvoltage Category	III	III	II
污染等级 Contamination Class	3	2	2
额定电压 Rated Voltage [V]	320	320	630
额定电流 Rated Current [A]	12	12	12
额定冲击电压 Impulse withstand voltage [KV]	4	4	4
导线截面积[硬/柔] Conductor cross section [mm²]	/		

材料 Material

绝缘材料 Insulation Material	PA66
--------------------------	------

WJ2EDGB-5.0/5.08

插拔式接线端子

下载日期:2024-05-06




阻燃等级 Flame relardant rating	UL94V-0
导体材料 Conductor Material	Copper alloy
导体表面镀层 Plating of conductor surface	Sn plated

一般参数 Other Data

间距/极数 Pitch/Poles [mm]/[P]	5.0 , 5.08/2-24
剥线长度 Stripping Length [mm]	/
螺丝/扭矩 Screw/Torque(Max)[N.m]	/
工作温度 Operating temperature [°C]	-40~+105
焊锡温度 Soldering temperature	260°C/5S
引针尺寸 Pin dimensions [mm]	0.4*1.1
PCB板孔径 PCB Hole Diameter [mm]	φ1.4

尺寸图

PCB开孔图



配件

WJ2EDGB-5.0/5.08

插拔式接线端子



下载日期:2024-05-06



WJ2EDGKDR-5.0/5.08

WJ2EDGKR-5.0/5.08


WJ2EDGKRZ-5.0/5.08



WJ2EDGRC-5.0/5.08

WJ2EDGV-THT-5.0/5.08


WJ2EDGVC-THT-5.0/5.08



WJ2EDGR-THT-5.0/5.08

WJ2EDGRC-THT-5.0/5.08

WJ2EDGRR-5.0/5.08



WJ2EDGRR-5.0/5.08

WJ2EDGR-5.0/5.08

WJ2EDGV-5.0/5.08

WJ2EDGB-5.0/5.08

插拔式接线端子

下载日期:2024-05-06



WJ2EDGVC-5.0/5.08