


WJ2EDGVM-7.5/7.62

插拔式接线端子

下载日期:2024-05-07



插拔式连接器
额定电流: 15 A
额定电压: 300 V
间距: 7.5 mm/7.62 mm
安装: 波峰焊



目录仅供参考，实际规格依产品工程图为准 版本1.0

技术数据-UL/CUL

等级 Use Group	B	C	D
额定电压 Rate Voltage [V]	300	-	300
额定电流 Rated Current [A]	15	-	10
接线范围 Wire Range [AWG]	/		
耐电压 Dielectric Voltage-Withstand	1.6KV		

技术参数-IEC

过电压类别 Overvoltage Category	III	III	II
污染等级 Contamination Class	3	2	2
额定电压 Rated Voltage [V]	400	630	630
额定电流 Rated Current [A]	15	15	15
额定冲击电压 Impulse withstand voltage [KV]	6	6	6
导线截面积[硬/柔] Conductor cross section [mm²]	/		

材料 Material

绝缘材料 Insulation Material	PA66
--------------------------	------

WJ2EDGVM-7.5/7.62

插拔式接线端子

下载日期:2024-05-07




WJ2EDGKM-7.5/7.62



WJ2EDGKAM-7.5/7.62



WJ2EDGKBM-7.5/7.62



WJ2EDGKDM-7.5/7.62