

Electrical Diagram :



For reference only!version1.0

CUL Technical Data (UL1059)

Use Group	B	C	D
Rated Voltage [V]	300	300	600
Rated Current [A]	15	15	5
Withstanding Voltage	1600V/1Min		
Wire Range	26-14AWG		

IEC Technical Data (IEC 60947-7-1)

Overvoltage Category	III
Contamination Class	3
Rated Voltage [V]	500V
Rated Current [A]	17.5A
Impulse withstand voltage	6KV

Conductor cross section

Soild	0.2-1.5mm ²
Flexible	0.2-1.5mm ²
Flexible with ferrule	0.2-1.5mm ²


Material

Insulation Material	PA66
Flame relardant rating	UL94V-0
Conductor Material	Copper alloy
Plating of conductor surface	Sn plated


Other Data

Length/Height/Thickness [mm]	72.4/35.4/4.2
Connection Points	4
Stripping Length [mm]	8-10
Type of rail	DIN 35
Screw/Torque(Max)[N.m]	/
Operating temperature [°C]	-40~+105


Dimensions




Accessories




[MUS1.5-10](#)




[FUSA1.5-XX](#)



[PUS1.5-120](#)




[EB-35](#)



[EW-35](#)



[DGL2-35x7.5A](#)



[DGL2-35x7.5B](#)



[DGL2-35x7.5C](#)



[DGL2-35x7.5D](#)



[DUV2.5-104](#)



[DGS1-35x7.5W4.2x12](#)



[DGS1-35x7.5W5.2x15](#)



[DGS1-35x7.5W](#)