




Electrical Diagram :



For reference only!version1.0

## CUL Technical Data (UL1059 )

| Use Group            | B        | C | D |
|----------------------|----------|---|---|
| Rated Voltage [V]    | /        | / | / |
| Rated Current [A]    | /        | / | / |
| Withstanding Voltage | /        |   |   |
| Wire Range           | 26-12AWG |   |   |

## IEC Technical Data (IEC 60947-7-2)

|                           |     |
|---------------------------|-----|
| Overvoltage Category      | III |
| Contamination Class       | 3   |
| Rated Voltage             | /   |
| Rated Current             | /   |
| Impulse withstand voltage | 8KV |

## Conductor cross section

|                       |                        |
|-----------------------|------------------------|
| Soild                 | 0.2-4mm <sup>2</sup>   |
| Flexible              | 0.2-2.5mm <sup>2</sup> |
| Flexible with ferrule | 0.2-2.5mm <sup>2</sup> |


Material

|                              |              |
|------------------------------|--------------|
| Insulation Material          | PA66         |
| Flame relardant rating       | UL94V-0      |
| Conductor Material           | Copper alloy |
| Plating of conductor surface | Sn plated    |


Other Data

|                              |               |
|------------------------------|---------------|
| Length/Height/Thickness [mm] | 60.6/35.4/5.2 |
| Connection Points            | 3             |
| Stripping Length [mm]        | 8-10          |
| Type of rail                 | DIN 35        |
| Screw/Torque(Max)[N.m]       | /             |
| Operating temperature [°C]   | -40~+105      |


Dimensions




Accessories



[MUV2.5-10](#)



[PUV2.5-96](#)



[FUVA2.5-XX](#)



[EB-35](#)



[EW-35](#)



[DGL2-35x7.5A](#)



[DGL2-35x7.5B](#)



[DGL2-35x7.5C](#)



[DGL2-35x7.5D](#)



[DUV2.5-103](#)



[DGS1-35x7.5W4.2x12](#)



[DGS1-35x7.5W5.2x15](#)



[DGS1-35x7.5W](#)