

Male Angled Field Assemble, Terminal Screw Type, Shielded

M12 Circular Connector

Download date : 2025-06-16



Connector : M12
Gender : Male
Coding : A,B,D
Locking Type : Fix Screw
Mounting Type : Field Assemble
Part No : M12-X**-RA2-M04-BS*
X:A,B,D Coding
**:03,04,05...8 (Pin)
*:1=Cable OD4.0~6.0MM
*:2=Cable OD6.0~8.0MM...

For reference only!version1.0

Technical Data

Standard	IEC61076
Ambient Temperatur	-25°C--+105°C
Insulation Resistance	$\geq 100\text{M}\Omega$
Contact Resistance	$\leq 5\text{m}\Omega$
IP Class	IP67
Mating Endurance	>100 Mating Cycles


Material Data

Connector Carriers	Copper Alloy With Nickel Plated 铜合金镀镍
Connector Contacts	Copper Alloy With Gold Plated 铜镀金
Connector Nut/Screw	Copper Alloy With Nickel Plated 铜合金镀镍
Seal/O-Ring	FKM 氟橡胶
Shielding	Shielded 屏蔽
Contacts Termination	Terminal Locking Screw 锁螺钉连接

Dimensions

Male Angled Field Assemble, Terminal Screw Type, Shielded
M12 Circular Connector

Download date : 2025-06-16



Specification Selection Table

Contacts Pin数	Available Coding 防插错编码			Rated Current 额定电流	Voltage 电压		Wire Range 接线范围		Part NO. 产品编号
	A-Coding	B-Coding	D-Coding		AC	DC	AWG	mm ²	
03Pins				4A	250V	250V	22	0.34	M12-A03-RA2-M04-BS* M12-B03-RA2-M04-BS*
04Pins				4A	250V	250V	22	0.34	M12-A04-RA2-M04-BS* M12-B04-RA2-M04-BS* M12-D04-RA2-M04-BS*
05Pins				4A	60V	60V	22	0.34	M12-A05-RA2-M04-BS* M12-B05-RA2-M04-BS*
08Pins				2A	30V	30V	24	0.25	M12-A08-RA2-M04-BS*