



PCB terminal block

Rated current: 12 A

Rated voltage: 300 V

Wire range: 26-14 AWG

Pitch: 5.08 mm

Mounting: Wave soldering



For reference only!version1.0

UL/CUL

Use Group	B	C	D
Rate Voltage [V]	300	-	300
Rated Current [A]	12	-	10
Wire Range [AWG]	26-14		
Dielectric Voltage-Withstand	1.6KV		

IEC

Overvoltage Category	III	III	II
Contamination Class	3	2	2
Rated Voltage [V]	250	400	630
Rated Current [A]	17.5	17.5	17.5
Impulse withstand voltage [KV]	4	4	4
Conductor cross section[solid/flexible] [mm²]	0.5-1.5		

Material

WJ127RF-5.08

PCB SCREW TERMINAL BLOCK

Download date : 2025-11-06



Insulation Material	PA66
Flame retardant rating	UL94V-0
Conductor Material	Copper alloy
Plating of conductor surface	Sn plated

Other Data

Pitch/Poles [mm]/[P]	5.08/2
Stripping Length [mm]	5-6
Screw/Torque(Max)[N.m]	M3/0.5
Operating temperature [°C]	-40°C~+105°C
Soldering temperature	260°C/5S
Pin dimensions [mm]	0.6*0.9
PCB Hole Diameter [mm]	Ø1.3

Dimensions

PCB opening diagram

