


Electrical Diagram :



For reference only!version1.0

CUL Technical Data (UL1059)

Withstanding Voltage	1600V/1Min
Wire Range	26-14AWG

IEC Technical Data (IEC 60947-7-2)

Overvoltage Category	III
Contamination Class	3
Impulse withstand voltage	6KV

Conductor cross section


Soild	0.2-1.5mm ²
Flexible	0.2-1.5mm ²
Flexible with ferrule	0.2-1mm ²

Material


Insulation Material	PA66
Flame relardant rating	UL94V-0
Conductor Material	Copper alloy

Plating of conductor surface	Sn plated
Other Data	
Length/Height/Thickness [mm]	45/30.6/3.5
Connection Points	2
Stripping Length [mm]	8-10
Type of rail	DIN 35
Screw/Torque(Max)[N.m]	/
Operating temperature [°C]	-40~+105


Dimensions




Accessories




[FUVA1.5-XX](#)




[MUV1.5-10](#)



[PUV1.5-144](#)




[EB-35](#)



[EW-35](#)



[DGL2-35x7.5A](#)



[DGL2-35x7.5B](#)



[DGL2-35x7.5C](#)




[DGL2-35x7.5D](#)



[DUV1.5-102](#)



[DGS1-35x7.5W4.2x12](#)



[DGS1-35x7.5W5.2x15](#)



[DGS1-35x7.5W](#)