



固定式连接器

额定电流: 20 A

额定电压: 300 V

使用线径: 26-12 AWG

间距: 5.0 mm/5.08 mm

安装: 波峰焊



目录仅供参考，实际规格依产品工程图为准 版本1.0

技术数据-UL/CUL

| 等级 Use Group                     | B     | C | D   |
|----------------------------------|-------|---|-----|
| 额定电压 Rate Voltage [V]            | 300   | - | 300 |
| 额定电流 Rated Current [A]           | 20    | - | 10  |
| 接线范围 Wire Range [AWG]            | 26~12 |   |     |
| 耐电压 Dielectric Voltage-Withstand | 1.6KV |   |     |

技术参数-IEC

|                                          |         |     |     |
|------------------------------------------|---------|-----|-----|
| 过电压类别 Overvoltage Category               | III     | III | II  |
| 污染等级 Contamination Class                 | 3       | 2   | 2   |
| 额定电压 Rated Voltage [V]                   | 250     | 400 | 630 |
| 额定电流 Rated Current [A]                   | 20      | 20  | 20  |
| 额定冲击电压 Impulse withstand voltage [KV]    | 4       | 4   | 4   |
| 导线截面积[硬/柔] Conductor cross section [mm²] | 0.5~2.5 |     |     |

材料 Material

|                                     |              |
|-------------------------------------|--------------|
| 绝缘材料 Insulation Material            | PA66         |
| 阻燃等级 Flame relardant rating         | UL94V-0      |
| 导体材料 Conductor Material             | Copper alloy |
| 导体表面镀层 Plating of conductor surface | Sn plated    |

一般参数 Other Data

|                                 |                     |
|---------------------------------|---------------------|
| 间距/极数 Pitch/Poles [mm]/[P]      | 5.0 , 5.08/2*2-2*24 |
| 剥线长度 Stripping Length [mm]      | 6~7                 |
| 螺丝/扭矩 Screw/Torque(Max)[N.m]    | M3/0.5              |
| 工作温度 Operating temperature [°C] | -40~+105            |
| 焊锡温度 Soldering temperature      | 260°C/5S            |
| 引针尺寸 Pin dimensions [mm]        | 0.8*1.0             |
| PCB板孔径 PCB Hole Diameter [mm]   | Ø1.5                |

尺寸图

PCB开孔图

