




弹簧式PCB连接器
额定电流: 20 A
额定电压: 300 V
使用线径: 28-12 AWG
间距: 7.5 mm
安装: 波峰焊



目录仅供参考，实际规格依产品工程图为准 版本1.0

技术数据-UL/CUL

等级 Use Group	B	C	D
额定电压 Rate Voltage [V]	300	150	300
额定电流 Rated Current [A]	20	20	10
接线范围 Wire Range [AWG]	28~12		
耐电压 Dielectric Voltage-Withstand	1.6KV		

技术参数-IEC

过电压类别 Overvoltage Category	III	III	II
污染等级 Contamination Class	3	2	2
额定电压 Rated Voltage [V]	500	630	1000
额定电流 Rated Current [A]	32	32	32
额定冲击电压 Impulse withstand voltage [KV]	6	6	6
导线截面积[硬/柔] Conductor cross section [mm²]	0.2~4.0		

材料 Material

一般参数 Other Data

间距/极数 Pitch/Poles [mm]/[P]	7.5/2~24
剥线长度 Stripping Length [mm]	9~10
螺丝/扭矩 Screw/Torque(Max)[N.m]	/
工作温度 Operating temperature [°C]	-40~+105
焊锡温度 Soldering temperature	260°C/5S
引针尺寸 Pin dimensions [mm]	1.2*0.8
PCB板孔径 PCB Hole Diameter [mm]	φ1.8

PCB开孔图

