




插拔式连接器
额定电流: 8 A
额定电压: 300 V
使用线径: 28-16 AWG
间距: 3.5 mm/3.81 mm



目录仅供参考，实际规格依产品工程图为准 版本1.0

技术数据-UL/CUL

等级 Use Group	B	C	D
额定电压 Rate Voltage [V]	300	-	300
额定电流 Rated Current [A]	8	-	8
接线范围 Wire Range [AWG]	28~16		
耐电压 Dielectric Voltage-Withstand	1.6KV		

技术参数-IEC

过电压类别 Overvoltage Category	III	III	II
污染等级 Contamination Class	3	2	2
额定电压 Rated Voltage [V]	160	160	250
额定电流 Rated Current [A]	7	7	7
额定冲击电压 Impulse withstand voltage [KV]	2.5	2.5	2.5
导线截面积[硬/柔] Conductor cross section [mm²]	0.5~1.5		

材料 Material


绝缘材料 Insulation Material	PA66
--------------------------	------

阻燃等级 Flame relardant rating	UL94V-0
导体材料 Conductor Material	Copper alloy
导体表面镀层 Plating of conductor surface	Ni plated


一般参数 Other Data

间距/极数 Pitch/Poles [mm]/[P]	3.5 , 3.81/2-24
剥线长度 Stripping Length [mm]	6-7
螺丝/扭矩 Screw/Torque(Max)[N.m]	M2/0.2
工作温度 Operating temperature [°C]	-40~+105
焊锡温度 Soldering temperature	/
引针尺寸 Pin dimensions [mm]	/
PCB板孔径 PCB Hole Diameter [mm]	/

尺寸图



配件




WJ15EDGVM-THR-3.5/3.81



WJ15EDGRM-THR-3.5/3.81



WJ15EDGKRN-3.81




WJ15EDGGBM-3.81




WJ15EDGLM-3.5/3.81



WJ15EDGVM-3.5/3.81




WJ15EDGRM-3.5/3.81



WJ15CDGM-3.81



WJ15EDGVTM-3.5/3.81



WJ15EDGRTM-3.5/3.81



WJ15EDGVHM-3.5/3.81



WJ15EDGRHM-3.5/3.81

