	插拔式连接器 额定电流: 10 A 额定电压: 300 V 使用线径: 28-12 AWG 间距: 7.5 mm/7.62 mm 接线方式: 直插式弹簧连接
---	--



目录仅供参考，实际规格依产品工程图为准 版本1.0

技术数据-UL/CUL

等级 Use Group	B	C	D
额定电压 Rate Voltage [V]	300	-	300
额定电流 Rated Current [A]	10	-	10
接线范围 Wire Range [AWG]	28-12		
耐电压 Dielectric Voltage-Withstand	1.6KV		

技术参数-IEC

过电压类别 Overvoltage Category	III	III	II
污染等级 Contamination Class	3	2	2
额定电压 Rated Voltage [V]	400	630	1000
额定电流 Rated Current [A]	12	12	12
额定冲击电压 Impulse withstand voltage [KV]	6	6	6
导线截面积[硬/柔] Conductor cross section [mm²]	0.2-2.5		

材料 Material


--	--

绝缘材料 Insulation Material	PA66
阻燃等级 Flame relardant rating	UL94V-0
导体材料 Conductor Material	Copper alloy
导体表面镀层 Plating of conductor surface	Sn plated


一般参数 Other Data

间距/极数 Pitch/Poles [mm]/[P]	7.5/2-24	7.62/2-16
剥线长度 Stripping Length [mm]	9-10	
螺丝/扭矩 Screw/Torque(Max)[N.m]	/	
工作温度 Operating temperature [°C]	-40~+105	
焊锡温度 Soldering temperature	/	
引针尺寸 Pin dimensions [mm]	/	
PCB板孔径 PCB Hole Diameter [mm]	/	

尺寸图



配件



WJ2EDGV-7.5/7.62



WJ2EDGR-7.5/7.62



WJ2EDGVC-7.5/7.62



WJ2EDGRC-7.5/7.62



WJ2EDGKR-7.62