





电路图：



目录仅供参考，实际规格依产品工程图为准 版本1.0

技术参数-UL (1059)

耐电压 Withstanding Voltage	1600V/1Min
接线范围 Wire Range	26-14AWG

技术参数-IEC(60947-7-2)

过电压类别 Overvoltage Category	III
污染等级 Contamination Class	3
额定冲击电压 Impulse withstand voltage	6KV

导线截面积 Conductor cross section


单芯 Solid	0.2-1.5mm ²
柔性导线 Flexible	0.2-1.5mm ²
柔性导线带冷压头 Flexible with ferrule	0.2-1mm ²

材料 Material


绝缘材料 Insulation Material	PA66
阻燃等级 Flame retardant rating	UL94V-0
导体材料 Conductor Material	Copper alloy

导体表面镀层 Plating of conductor surface	Sn plated
一般参数 Other Data	
长/高/厚 Length/Height/Thickness [mm]	45/30.6/3.5
连接点数 Connection Points	2
剥线长度 Stripping Length [mm]	8-10
导轨类型 Type of rail	DIN 35
螺丝/扭矩 Screw/Torque(Max)[N.m]	/
工作温度 Operating temperature [°C]	-40~+105


尺寸图




配件




FUVA1.5-XX




MUV1.5-10



PUV1.5-144




EB-35



EW-35



DGL2-35x7.5A



DGL2-35x7.5B



DGL2-35x7.5C



DGL2-35x7.5D



DUV1.5-102



DGS1-35x7.5W4.2x12



DGS1-35x7.5W5.2x15



DGS1-35x7.5W