M8 Female Panel Mount, Solder Type, Front Fastened M8 Circular Connector Download Date:2025-12-16



M08-X**-ST0-F02-BQ3









The catalog is for reference only. The actual

specifications are subject to the product

engineering drawings. version 1.0


Connector Series: M8

Gender	Female		
Coding	А,В		
Locking Type	Fix Screw		
Mounting Type	Front Fastened		
Part No	M08-X**-ST0-F02-BQ3		

Technical Data

Standard	IEC61076-2-104			
Ambient Temperatur	-25℃~+85℃			
Insulation Resistance	≥100MΩ			
Contact Resistance	≤5mΩ			

M8 Female Panel Mount, Solder Type, Front Fastened Download Date:2025-12-16





IP Class	IP67						
Mating Endurance	>100 Mating Cycles						
Material Data							
Connector Carriers	PA						
Connector Contacts	Copper Alloy With Gold Plated						
Connector Nut/Screw	Copper Alloy With Nickel Plated						
Shielding	Unshielded						
Seal/O-Ring	FKM						
Electrical Data & Mechanical Date							
Contacts Pin [Pins]	3	4	5	6	8		
Rated Current [A]	3	3	3	1.5	1.5		
Voltage AC/DC [V]	50/60	50/60	30/30	30/30	30/30		
Wire Range [AWG/mm²]	24/0.25	24/0.25	24/0.25	26/0.14	26/0.14		

Dimensions

PCB hole diagram

