

M08-X**-ST0-F01-BQ3









The catalog is for reference only. The actual

specifications are subject to the product

engineering drawings. version 1.0

Connector Series: M8

Gender	Female
Coding	А,В
Locking Type	Fix Screw
Mounting Type	Front Fastened
Part No	M08-X**-ST0-F01-BQ3
echnical Data	<u>'</u>

Standard	IEC61076-2-104
Ambient Temperatur	-25℃~+85℃
Insulation Resistance	≥100MΩ
Contact Resistance	≤5mΩ

M8 Female Panel Mount, PCB Type, Front Fastened Download Date:2025-12-17





IP Class	IP67					
Mating Endurance	>100 Mating Cycles					
Material Data						
Connector Carriers	PA					
Connector Contacts	Copper Alloy With Gold Plated					
Connector Nut/Screw	Copper Alloy With Nickel Plated					
Shielding	Unshielded					
Seal/O-Ring	FKM					
Electrical Data & Mechanical Date						
Contacts Pin [Pins]	3	4	5	6	8	
Rated Current [A]	3	3	3	1.5	1.5	
Voltage AC/DC [V]	50/60	50/60	30/30	30/30	30/30	
Contacts Termination	PCB Version					

Dimensions

PCB hole diagram

