

M12 Female Molded Cables, Straight, Shielded



The catalog is for reference only. The actual specifications are subject to the product engineering drawings. version 1.0

Connector Series: M12

| | |
|---------------|-------------------------|
| Gender | Female |
| Coding | A,B,C,D |
| Locking Type | Fix Screw |
| Mounting Type | Straight |
| Part No | M12-X**-ST2-F02-BC*-XXX |

Technical Data

| | |
|-----------------------|----------------|
| Standard | IEC61076-2-101 |
| Ambient Temperatur | -25°C~+80°C |
| Insulation Resistance | ≥100MΩ |
| Contact Resistance | ≤5mΩ |

| | |
|------------------|--------------------|
| IP Class | IP67 |
| Mating Endurance | >100 Mating Cycles |

Material Data

| | |
|---------------------|---------------------------------|
| Connector Carriers | PA |
| Connector Contacts | Copper Alloy With Gold Plated |
| Connector Nut/Screw | Copper Alloy With Nickel Plated |
| Seal/O-Ring | FKM |
| Shielding | Shielding |
| Connector Overmold | TPU |

Electrical Data & Mechanical Date

| | | | | | | | |
|--------------------------------|---------|---------|--------------------------|---------|---------|---------|---------|
| Contacts Pin [Pins] | 3 | 4 | 5 | 6 | 8 | 12 | 17 |
| Rated Current [A] | 4 | 4 | 4/2 | 2 | 2 | 1.5 | 1.5 |
| Voltage AC/DC [V] | 250/250 | 250/250 | 60/60 | 30/30 | 30/30 | 30/30 | 30/30 |
| Wire Range AWG/mm ² | 22/0.34 | 22/0.34 | 22,24/0.34,0.25 (C-code) | 24/0.25 | 24/0.25 | 26/0.14 | 26/0.14 |
| Cable Jacket | PUR/PVC | | | | | | |

Dimensions

M12-X**-ST2-F02-BC*-XXX

M12 Circular Connector

Download Date:2026-06-30

