M12 Male Molded Cables, X Coding, Straight Download Date:2025-12-17





M12-X**-ST0-M02-BC*-XXX







The catalog is for reference only. The actual specifications are subject to the product

engineering drawings. version 1.0

Connector Series: M12

Gender	Male
Coding	X
ocking Type	Fix Screw
Nounting Type	Straight
art No	M12-X**-ST0-M02-BC*-XXX
echnical Data	<u>'</u>

Standard	IEC61076-2-109
Ambient Temperatur	-25℃~+80℃
Insulation Resistance	≥100MΩ
Contact Resistance	≤5mΩ

M12 Male Molded Cables, X Coding, Straight M12 Circular Connector Download Date:2025-12-17





IP Class	IP67	
Mating Endurance	>100 Mating Cycles	
Material Data		
Connector Carriers	PA	
Connector Contacts	Copper Alloy With Gold Plated	
Connector Nut/Screw	Copper Alloy With Nickel Plated	
Shielding	Unshielded/Shielded	
Connector Overmold	TPU	
Electrical Data & Mechanical Date		
Auailable Coding	X-Coding	
Contacts Pin (Pins)	08	
Rated Current [A]	0.5	
Rated Voltage [V][AC/DC]	50/60	
Wire Range AWG/mm²	26-24/0.14-0.25	
Cable Jacket	PUR/PVC	

Dimensions

M12 Male Molded Cables, X Coding, Straight M12 Circular Connector Download Date:2025-12-17





