


Male Molded 2 Cables, Straight



The catalog is for reference only. The actual specifications are subject to the product engineering drawings. version 1.0

Connector Series: M12

Gender	Male
Coding	A,B,C,D
Locking Type	Fix Screw
Mounting Type	Straight
Part No	M12-X**-ST0-M02-BV*-XXX

Technical Data

Standard	IEC61076-2-101
Ambient Temperatur	-25°C~+80°C
Insulation Resistance	≥100MΩ
Contact Resistance	≤5mΩ

IP Class	IP67
Mating Endurance	>100 Mating Cycles

Material Data

Connector Carriers	PA
Connector Contacts	Copper Alloy With Gold Plated
Connector Nut/Screw	Copper Alloy With Nickel Plated
Shielding	UnShielding/Shielding
Connector Overmold	TPU

Electrical Data & Mechanical Date

Contacts Pin [Pins]	3	4	5	6	8
Rated Current [A]	4	4	4/2	2	2
Voltage AC/DC [V]	250/250	250/250	60/60	30/30	30/30
Wire Range AWG/mm ²	22/0.34	22/0.34	22,24/0.3 4,0.25 (C- code)	24/0.25	24/0.25
Cable Jacket	PUR/PVC				

Dimensions

M12-X**-ST0-M02-BV*-XXX

M12 Circular Connector

Download Date:2026-06-29

