







The catalog is for reference only. The actual specifications are subject to the product

engineering drawings. version 1.0

Connector Series: 7/8"

| Gender | Female | | | |
|---------------|-------------------------|--|--|--|
| Coding | A | | | |
| Locking Type | Fix Screw | | | |
| Mounting Type | Angled | | | |
| Part No | M87-A**-RA0-F02-BC*-XXX | | | |

Technical Data

| Ambient Temperatur | -25℃~+85℃ | | | |
|-----------------------|-----------|--|--|--|
| Insulation Resistance | ≥100MΩ | | | |
| Contact Resistance | ≤5mΩ | | | |
| IP Class | IP67 | | | |

7/8" Female Molded Cables, Angled

7/8" Circular Connector

Download Date: 2025-12-15



| Mating Endurance | >100 Mating Cycles | | | | | |
|-----------------------------------|---------------------------------|----|----|---|--|--|
| Material Data | | | | | | |
| Connector Carriers | PA | | | | | |
| Connector Contacts | Copper Alloy With Gold Plated | | | | | |
| Connector Nut/Screw | Copper Alloy With Nickel Plated | | | | | |
| Shielding | Unshielded | | | | | |
| Seal/O-Ring | KFM | | | | | |
| Connector Overmold | TPU | | | | | |
| Electrical Data & Mechanical Date | | | | | | |
| Contacts Pin [Pins] | 2 | 3 | 4 | 5 | | |
| Rated Current [A] | 13 | 13 | 13 | 8 | | |
| Voltage AC/DC [V] | 300/300 | | | | | |
| Wire Range AWG/mm² | 16/1.5 | | | | | |
| Cable Jacket | PVC/PUR | | | | | |

Dimensions



