







The catalog is for reference only. The actual

specifications are subject to the product

engineering drawings. version 1.0

Connector Series: 7/8"

Gender	Male to Female			
Coding	А			
Locking Type	Fix Screw			
Mounting Type	Т Туре			
Part No	M87-A**-ST0-MF2-BT*-XXX			

Technical Data

Ambient Temperatur	-25℃~+85℃			
Insulation Resistance	≥100MΩ			
Contact Resistance	≤5mΩ			
IP Class	IP67			

7/8" T Type Male-Female Molded With Cable Download Date:2025-12-16





Mating Endurance	>100 Mating Cycles					
Material Data						
Connector Carriers	PA					
Connector Contacts	Copper Alloy With Gold Plated					
Connector Nut/Screw	Copper Alloy With Nickel Plated					
Shielding	Unshielded					
Seal/O-Ring	FKM					
Connector Overmold	TPU					
Electrical Data & Mechanical Date						
Contacts Pin [Pins]	2	3	4	5		
Rated Current [A]	13	13	13	7		
Voltage AC/DC [V]	300/300					
Wire Range AWG/mm²	18/1.0	18/1.0	18/1.0	20/0.5		
Cable Jacket	PVC/PUR					

Dimensions

7/8" T Type Male-Female Molded With Cable 7/8" Circular Connector Download Date:2025-12-16





