



M16 Male Panel Mount, Solder Type, Front Fastened

The catalog is for reference only. The actual specifications are subject to the product engineering drawings. version 1.0

Connector Series: M16

Gender	Male
Coding	A , B
Locking Type	Fix Screw
Mounting Type	Front Fastened
Part No	M16-A**-ST0-M01-ZQ2

Technical Data

Standard	IEC61076-2-106
Ambient Temperatur	-25°C~+85°C
Insulation Resistance	≥100MΩ
Contact Resistance	≤5mΩ

IP Class	IP67
Mating Endurance	>100 Mating Cycles


Material Data

Connector Carriers	PA
Connector Contacts	Copper Alloy With Gold Plated
Connector Nut/Screw	Zn Alloy With Nickel Plated
Shielding	Unshielded
Seal/O-Ring	FKM

Electrical Data & Mechanical Date

Contacts Pin [Pins][Coding]	3-A 4-A 5-A 5-B 6-A 7-A 7-B 8-A 14-A 16-A 19-A 24-A
Rated Current [A]	7 6 6 6 5 5 5 5 3 3 3 1
电压 Voltage AC/DC [V]	250 250 250 60/ 250 125 60/ 60/ 60/ 60/ 60/ 60/ /32 /32 /32 32 /32 /32 32 32 32 32 32
Contacts Termination	PCB Version

Dimensions



Accessories



M16-A**-ST0-F02-BC*-XXX



M16-A**-RA0-F02-BC*-XXX



M16-A**-ST0-F02-BQ2-XXX



M16-A**-ST0-F02-BH2-XXX



M16-A**-ST0-F02-BQ2



M16-A**-ST0-F02-BH2



M16-A**-ST0-F01-BQ2