

Rated current: 10A

Rated voltage: 300V

Use wire diameter: 24-14AWG

spacing:7.5mm

The catalog is for reference only. The actual specifications are subject to the product engineering drawings. version 1.0

UL/CUL

Use Group	B	C	D
Rate Voltage [V]	300	-	300
Rated Current [A]	10	-	10
Wire Range [AWG]	24～14		
Dielectric Voltage-Withstand	1.6KV		

IEC

Overvoltage Category	III	III	II
Contamination Class	3	2	2
Rated Voltage [V]	500	630	1000
Rated Current [A]	15	15	15

Impulse withstand voltage [KV]	6	6	6
Conductor cross section [mm²]	0.2~1.5		

Material


Insulation Material	PA66
Flame relardant rating	UL94V-0
Conductor Material	Copper alloy
Plating of conductor surface	Sn plated


Other Date

Pitch/Poles [mm]/[P]	7.5/2-24
Stripping Length [mm]	10
Screw/Torque(Max)[N.m]	-
Operating temperature [℃]	-40～+105
Soldering method	Wave soldering
Pin dimensions [mm]	1.0*0.5
PCB Hole Diameter [mm]	Ø1.4

Dimensions

PCB hole diagram


13.3(REF)
10.60
14.05
0.50
7.62
1.50
3.50
7.50XX
7.50
1.00
7.50(XX-1)
2.82


7.50
7.62
1.50
14.05
Ø1.40
7.50(XX-1)
2.82
P.C.B. LAYOUT