



Rated current: 115A
Rated voltage: 600V
Use wire diameter: 20-2AWG
spacing:15.0mm
Install: Wave soldering



The catalog is for reference only. The actual specifications are subject to the product engineering drawings. version 1.0

UL/CUL

Use Group	B	C	D
Rate Voltage [V]	600	600	600
Pated Current [A]	115	115	5
Wire Range [AWG]	20~2		
Dielectric Voltage-Withstand	2.2KV		

IEC

Overvoltage Category	III	III	II
Contamination Class	3	2	2
Rated Voltage [V]	1000	1000	1000
Rated Current [A]	125	125	125

Impulse withstand voltage [KV]	8	8	8
Conductor cross section [mm ²]	0.5~35		

Material

Insulation Material	PA66
Flame retardant rating	UL94V-0
Conductor Material	Copper alloy
Plating of conductor surface	Sn plated

Other Data

Pitch/Poles [mm]/[P]	15.0/2-10
Stripping Length [mm]	17-18
Screw/Torque(Max)[N.m]	M5/2.0
Operating temperature [°C]	-40 ~ +105
Soldering method	Wave soldering
Pin dimensions [mm]	1.2*1.2
PCB Hole Diameter [mm]	Ø2.0

Dimensions

PCB hole diagram

