



Rated current: 15A  
Rated voltage: 300V  
Use wire diameter: 28-12AWG  
spacing:7.62mm



The catalog is for reference only. The actual specifications are subject to the product engineering drawings. version 1.0

### UL/CUL

Use Group	B	C	D
Rate Voltage [V]	300	-	300
Rated Current [A]	15	-	10
Wire Range [AWG]	28-12		
Dielectric Voltage-Withstand	1.6KV		

### IEC

Overvoltage Category	III	III	II
Contamination Class	3	2	2
Rated Voltage [V]	400	630	1000
Rated Current [A]	24	24	24

Impulse withstand voltage [KV]	6	6	6
导体Conductor cross section [mm <sup>2</sup> ]	0.2-2.5		

### Material

Insulation Material	PA66
Flame retardant rating	UL94V-0
Conductor Material	Copper alloy
Plating of conductor surface	Sn plated

### Other Date

Pitch/Poles [mm]/[P]	7.62/2-30
Stripping Length [mm]	5-6
Screw/Torque(Max)[N.m]	-
Operating temperature [°C]	-40 ~ +105
Soldering method	Wave soldering
Pin dimensions [mm]	0.75*0.7
PCB Hole Diameter [mm]	Ø1.3

### Dimensions

### PCB hole diagram

