




额定电流: 15A

额定电压: 300V

使用线径: 22-14AWG

间距:8.5mm



目录仅供参考，实际规格依产品工程图为准 版本1.0

材质及电镀 Material

| | |
|---------------|--------------------------|
| 螺丝 Screws | M3.0 Steel Ni plated |
| 焊脚 Pin Header | Copper alloy , Sn plated |
| 塑件 Housing | PA66 , UL94V-0 |

电气性能 Electrical

| | | |
|----------------------------|--------------|--------------------|
| 参考标准 Standard | UL | IEC |
| 额定电压 Rated voltage | 300V | 450V |
| 额定电流 Rated current | 15A | 17.5A |
| 使用线径 Wire range | 22-14AWG | 1.5mm ² |
| 接触电阻 Contact Resistance | 20mΩ | |
| 绝缘电阻 Insulation resistance | 500MΩ/DC500V | |
| 耐电压 Withstanding voltage | AC2000V/1Min | |

一般参数 Other Date

| | |
|---------------------------------|----------------------------|
| 间距/极数 Pitch/Poles [mm]/[P] | 8.5/2-25 |
| 工作温度 Operating temperature [°C] | -40 ~ +105 |
| 扭矩 Torque | 5.1Kgf.cm/0.5N.m/4.43Lb.in |

尺寸图

PCB开孔图

