



额定电流: 40A

额定电压: 600V

使用线径: 22-8AWG

间距:13.0mm

目录仅供参考，实际规格依产品工程图为准 版本1.0

技术数据-UL/CUL

等级 Use Group	B	C	D
额定电压 Rate Voltage [V]	600	600	600
额定电流 Rated Current [A]	40	40	5
接线范围 Wire Range [AWG]	22-8		
耐电压 Dielectric Voltage-Withstand	2.2KV		

技术参数-IEC

过电压类别 Overvoltage Category	III	III	II
污染等级 Contamination Class	3	2	2
额定电压 Rated Voltage [V]	800	800	1000
额定电流 Rated Current [A]	40	40	40
额定冲击电压 Impulse withstand voltage [KV]	8	8	8

导线截面积[硬/柔] Conductor cross section [mm ²]	6
材料 Material	
绝缘材料 Insulation Material	PBT
阻燃等级 Flame retardant rating	UL94V-0
导体材料 Conductor Material	Copper alloy
导体表面镀层 Plating of conductor surface	Sn plated
一般参数 Other Data	
间距/极数 Pitch/Poles [mm]/[P]	13.0/2-18
剥线长度 Stripping Length [mm]	10-11
螺丝/扭矩 Screw/Torque(Max)[N.m]	M4/1.2
工作温度 Operating temperature [°C]	-30 ~ +120
焊接方式 Soldering method	Wave soldering
引针尺寸 Pin dimensions [mm]	1.0*2.0
PCB板孔径 PCB Hole Diameter [mm]	1.7*2.7

尺寸图

PCB开孔图

