



额定电流: 20A

额定电压: 600V

使用线径: 28-12AWG



目录仅供参考，实际规格依产品工程图为准 版本1.0

技术数据-UL (1059)

等级 Use Group	B	C	D
额定电压 Rate Voltage [V]	600	600	600
额定电流 Rated Current [A]	20	20	5
接线范围 Wire Range [AWG]	28-12		
耐电压 Dielectric Voltage-Withstand [KV]	2.2		

技术参数-IEC

额定电压 Rated Voltage [V]	800
额定电流 Rated Current [A]	24
导线截面积[硬/柔] Conductor cross section [mm ²]	0.5-2.5
过电压类别 Overvoltage Category	III
污染等级 Contamination Class	3

额定冲击电压 Impulse withstand voltage [KV]	8
---------------------------------------	---

材料 Material

绝缘材料 Insulation Material	PA66
阻燃等级 Flame retardant rating	UL94V-0
导体材料 Conductor Material	Copper alloy
导体表面镀层 Plating of conductor surface	Sn plated

一般参数 Other Date

间距/极数 Pitch/Poles [mm]/[P]	10.0/1-24
剥线长度 Stripping Length [mm]	9-10
工作温度 Operating temperature [°C]	-40~+105

尺寸图

