



固定式连接器

额定电流: 30A

额定电压: 600V

使用线径: 24-10AWG

间距:6.35mm

安装: 波峰焊



目录仅供参考，实际规格依产品工程图为准 版本1.0

## 技术数据-UL/CUL

等级 Use Group	B	C	D
额定电压 Rate Voltage [V]	600	600	600
额定电流 Rated Current [A]	30	30	5
接线范围 Wire Range [AWG]		24 ~ 10	
耐电压 Dielectric Voltage-Withstand		2.2KV	

## 技术参数-IEC

过电压类别 Overvoltage Category	III	III	II
污染等级 Contamination Class	3	2	2
额定电压 Rated Voltage [V]	800	1000	1000
额定电流 Rated Current [A]	41	41	41
额定冲击电压 Impulse withstand voltage [KV]	8	8	8

导线截面积[硬/柔] Conductor cross section [mm<sup>2</sup>]

0.2~6.0/0.2~4.0

## 材料 Material

绝缘材料 Insulation Material

PA66

阻燃等级 Flame retardant rating

UL94V-0

导体材料 Conductor Material

Copper alloy

导体表面镀层 Plating of conductor surface

Sn plated

## 一般参数 Other Date

间距/极数 Pitch/Poles [mm]/[P]

6.35/2-18

剥线长度 Stripping Length [mm]

8

螺丝/扭矩 Screw/Torque(Max)[N.m]

M3/0.5

工作温度 Operating temperature [°C]

-40 ~ +105

焊接方式 Soldering method

Wave soldering

引针尺寸 Pin dimensions [mm]

0.9\*0.9

PCB板孔径 PCB Hole Diameter [mm]

Ø1.5

尺寸图

PCB开孔图

# WJ635VK-6.35

螺钉式PCB接线端子

下载日期:2026-05-12

