



额定电流: 40A

额定电压: 600V

使用线径: 24-8AWG

间距:7.5mm



目录仅供参考，实际规格依产品工程图为准 版本1.0

### 技术数据-UL/CUL

| 等级 Use Group                     | B     | C   | D   |
|----------------------------------|-------|-----|-----|
| 额定电压 Rate Voltage [V]            | 600   | 600 | 600 |
| 额定电流 Rated Current [A]           | 40    | 40  | 5   |
| 接线范围 Wire Range [AWG]            | 24-8  |     |     |
| 耐电压 Dielectric Voltage-Withstand | 2.2KV |     |     |

### 技术参数-IEC

| 过电压类别 Overvoltage Category            | III | III  | II   |
|---------------------------------------|-----|------|------|
| 污染等级 Contamination Class              | 3   | 2    | 2    |
| 额定电压 Rated Voltage [V]                | 800 | 1000 | 1000 |
| 额定电流 Rated Current [A]                | 41  | 41   | 41   |
| 额定冲击电压 Impulse withstand voltage [KV] | 8   | 8    | 6    |

|   |                |
|---|----------------|
| 导线截面积[硬/柔] Conductor cross section [mm <sup>2</sup> ] | 0.2~10/0.2~6   |
| <b>材料 Material</b>                                    |                |
| 绝缘材料 Insulation Material                              | PA66           |
| 阻燃等级 Flame retardant rating                           | UL94V-0        |
| 导体材料 Conductor Material                               | Copper alloy   |
| 导体表面镀层 Plating of conductor surface                   | Sn plated      |
| <b>一般参数 Other Data</b>                                |                |
| 间距/极数 Pitch/Poles [mm]/[P]                            | 7.5/2-18       |
| 剥线长度 Stripping Length [mm]                            | 15             |
| 螺丝/扭矩 Screw/Torque(Max)[N.m]                          | -              |
| 工作温度 Operating temperature [°C]                       | -40 ~ +105     |
| 焊接方式 Soldering method                                 | Wave soldering |
| 引针尺寸 Pin dimensions [mm]                              | 1.7*0.8        |
| PCB板孔径 PCB Hole Diameter [mm]                         | Ø2.1           |

尺寸图

PCB开孔图

