



GUV6-103-PE

GUV Push-in terminal block

Download date : 2024-05-07



Electrical Diagram :



For reference only!version1.0

CUL Technical Data (UL1059)

Withstanding Voltage	2200V/1Min
Wire Range	20-8AWG

IEC Technical Data (IEC 60947-7-2)

Overvoltage Category	III
Contamination Class	3
Impulse withstand voltage	8KV

Conductor cross section

Soild	0.5-10mm²
Flexible	0.5-6mm²
Flexible with ferrule	0.5-6mm²

Material

Insulation Material	PA66
Flame relardant rating	UL94V-0
Conductor Material	Copper alloy

GUV6-103-PE


GUV Push-in terminal block

Download date : 2024-05-07




Plating of conductor surface	Sn plated
Other Data	
Length/Height/Thickness [mm]	74.2/42.3/8.2
Connection Points	3
Stripping Length [mm]	10-12
Type of rail	DIN 35
Screw/Torque(Max)[N.m]	/
Operating temperature [°C]	-40~+105


Dimensions




Accessories




[FUVA6-XX](#)




[MUV6-10](#)



[PUV6-56](#)



[EB-35](#)



[EW-35](#)



[DGL2-35x7.5A](#)



[DGL2-35x7.5B](#)



[DGL2-35x7.5C](#)



[DGL2-35x7.5D](#)



[DUV6-103](#)



[DGS1-35x7.5W4.2x12](#)



[DGS1-35x7.5W5.2x15](#)



[DGS1-35x7.5W](#)