




Electrical Diagram :



For reference only!version1.0

CUL Technical Data (UL1059)

Withstanding Voltage	2200V/1Min
Wire Range	20-6AWG

IEC Technical Data (IEC 60947-7-2)

Overvoltage Category	III
Contamination Class	3
Impulse withstand voltage	8KV

Conductor cross section

Soild	0.5-16mm ²
Flexible	0.5-10mm ²
Flexible with ferrule	0.5-10mm ²

Material


Insulation Material	PA66
Flame relardant rating	UL94V-0
Conductor Material	Copper alloy

Plating of conductor surface	Sn plated
------------------------------	-----------

Other Data

Length/Height/Thickness [mm]	89.2/49.7/10.2
Connection Points	3
Stripping Length [mm]	18
Type of rail	DIN 35
Screw/Torque(Max)[N.m]	/
Operating temperature [°C]	-40~+105

Dimensions




Accessories




[FUVA10-XX](#)




[MUV10-10](#)



[PUV10-48](#)




[EB-35](#)




[EW-35](#)



[DGL2-35x7.5A](#)



[DGL2-35x7.5B](#)



[DGL2-35x7.5C](#)



[DGL2-35x7.5D](#)



[DUV10-103](#)



[DGS1-35x7.5W4.2x12](#)



[DGS1-35x7.5W5.2x15](#)



[DGS1-35x7.5W](#)