



连接器系列：M12
类型：母
编码：S,T
装配方式：锁螺丝
安装类型：前锁
产品编号：M12-X**-ST0-F03-BQ*-XXX
X:S,T Coding(S,T扣)
**:03,04(Pin数)
*:1=M16X1.5 2=PG9,...

XXX:050=0.5M,100=1M,10M=10M...(Length长度)



目录仅供参考，实际规格依产品工程图为准 版本1.0

技术参数 Technical Data

标准 Standard	IEC61076-2-111
工作温度 Ambient Temperatur	-25°C~+80°C
绝缘电阻 Insulation Resistance	≥100MΩ
接触电阻 Contact Resistance	≤10mΩ
防护等级 IP Class	IP67
机械寿命 Mating Endurance	>100 Mating Cycles


材质说明 Material Data

胶芯材料 Connector Carriers	PA
接触端子 Connector Contacts	Copper Alloy With Gold Plated 铜镀金
螺母/螺丝 Connector Nut/Screw	Copper Alloy With Nickel Plated 铜镀镍
密封胶圈 Seal/O-Ring	FKM 氟橡胶
屏蔽 Shielding	Unshielded 非屏蔽
连接方式 Contacts Termination	Crimping Type 压接式

电气参数&机械参数 Electrical Data & Mechanical Date

防插错编码 Available Coding	S-Coding	T-Coding
额定电流 Rated Current	16A(03Pin) 12A(04Pin)	12A
额定电压 Rated Voltage	630V	60V
接线范围 Wire Range AWG/mm ²	16 AWG / 1.5 mm ²	

尺寸图



规格选型表 Specification Selection Table

Available Coding 防插错编码	Contacts Pin 芯数		Rated Current 额定电流	Rated Voltage 额定电压	Wire Range 接线范围		Part NO. 产品编号
	03Pins	04Pins			AWG	mm ²	
S-Coding			16A(03Pin) 12A(04Pin)	630V	16	1.5	M12-S03-ST0-F03-BQ*-XXX M12-S04-ST0-F03-BQ*-XXX
T-Coding			12A	60V	16	1.5	M12-T03-ST0-F03-BQ*-XXX M12-T04-ST0-F03-BQ*-XXX

配套部件 Matching Parts



M12 公头成型式线缆，S&T-
Coding直头