



插拔式连接器
额定电流: 15 A
额定电压: 300 V
使用线径: 28-12 AWG
间距: 5.0 mm/5.08 mm



目录仅供参考，实际规格依产品工程图为准 版本1.0

技术数据-UL/CUL

等级 Use Group	B	C	D
额定电压 Rate Voltage [V]	300	-	300
额定电流 Rated Current [A]	15	-	10
接线范围 Wire Range [AWG]	28~12		
耐电压 Dielectric Voltage-Withstand	1.6KV		

技术参数-IEC

过电压类别 Overvoltage Category	III	III	II
污染等级 Contamination Class	3	2	2
额定电压 Rated Voltage [V]	250	320	630
额定电流 Rated Current [A]	15	15	15
额定冲击电压 Impulse withstand voltage [KV]	4	4	4
导线截面积[硬/柔] Conductor cross section [mm²]	0.2~2.5		

材料 Material


绝缘材料 Insulation Material	PA66
--------------------------	------

阻燃等级 Flame relardant rating	UL94V-0
导体材料 Conductor Material	Copper alloy
导体表面镀层 Plating of conductor surface	Ni plated

一般参数 Other Data

间距/极数 Pitch/Poles [mm]/[P]	5.0 , 5.08/2~24
剥线长度 Stripping Length [mm]	7-8
螺丝/扭矩 Screw/Torque(Max)[N.m]	M3/0.5
工作温度 Operating temperature [°C]	-40~+105
焊锡温度 Soldering temperature	/
引针尺寸 Pin dimensions [mm]	/
PCB板孔径 PCB Hole Diameter [mm]	/

尺寸图



配件




WJ2EDGVM-5.0/5.08



WJ2EDGRM-5.0/5.08



WJ2EDGVM-THT-5.0/5.08




WJ2EDGRRM-5.0/5.08



WJ2EDGVMT-5.0/5.08




WJ2EDGRM-THT-5.0/5.08




WJ2EDGRTM-5.0/5.08




WJ2EDGVHM-5.0/5.08



WJ2EDGRHM-5.0/5.08




WJ2EDGLM-5.0/5.08



WJ2EDGKDRN-5.0/5.08



WJ2EDGKRN-5.0/5.08



WJ2CDGM-5.0/5.08