




插拔式连接器  
额定电流: 10 A  
额定电压: 300 V  
使用线径: 26-16 AWG  
间距: 3.5 mm  
接线方式: 直插式弹簧连接



目录仅供参考，实际规格依产品工程图为准 版本1.0

技术数据-UL/CUL

| 等级 Use Group                     | B     | C  | D   |
|----------------------------------|-------|----|-----|
| 额定电压 Rate Voltage [V]            | 300   | 50 | 300 |
| 额定电流 Rated Current [A]           | 10    | 10 | 10  |
| 接线范围 Wire Range [AWG]            | 26~16 |    |     |
| 耐电压 Dielectric Voltage-Withstand | 1.6KV |    |     |

技术参数-IEC

|                                          |         |      |      |
|------------------------------------------|---------|------|------|
| 过电压类别 Overvoltage Category               | III     | III  | II   |
| 污染等级 Contamination Class                 | 3       | 2    | 2    |
| 额定电压 Rated Voltage [V]                   | 160     | 160  | 320  |
| 额定电流 Rated Current [A]                   | 13.4    | 13.4 | 13.4 |
| 额定冲击电压 Impulse withstand voltage [KV]    | 2.5     | 2.5  | 2.5  |
| 导线截面积[硬/柔] Conductor cross section [mm²] | 0.2-1.5 |      |      |


材料 Material

|                                     |              |
|-------------------------------------|--------------|
| 绝缘材料 Insulation Material            | PA66         |
| 阻燃等级 Flame relardant rating         | UL94V-0      |
| 导体材料 Conductor Material             | Copper alloy |
| 导体表面镀层 Plating of conductor surface | Sn plated    |

一般参数 Other Data

|                                 |              |
|---------------------------------|--------------|
| 间距/极数 Pitch/Poles [mm]/[P]      | 3.5/2*2-2*24 |
| 剥线长度 Stripping Length [mm]      | 10-11        |
| 螺丝/扭矩 Screw/Torque(Max)[N.m]    | /            |
| 工作温度 Operating temperature [°C] | -40~+105     |
| 焊锡温度 Soldering temperature      | /            |
| 引针尺寸 Pin dimensions [mm]        | /            |
| PCB板孔径 PCB Hole Diameter [mm]   | /            |


尺寸图




配件




WJ15EDGVHSM-3.5



WJ15EDGRHSM-3.5



WJ15EDGVHSM-THR-3.5



WJ15EDGRHSM-THR-3.5