


Transfer or dupli



variable range	to	over 6 to	over 10 to	over 30 to	over 60 to	over 100 to	over 160 to	to	over 10 to	over 100 to
----------------	----	-----------	------------	------------	------------	-------------	-------------	----	------------	-------------

4	Pin	Copper Alloy	M3/Sn Plated
3	Screw	Steel	M3/Zn Plated
2	Spring	Stainless Steel	
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
V0	新发行		CY	23.11.28

UL/CUL 技术参数		C  US		
UL/CUL Technical Data				
等级	Use Group	B	C	D
额定电压	Rated Voltage [V]	250	-	250
额定电流	Rated Current [A]	16	-	10
接线范围	Wire Range	22-14		
单/多芯线	Solid/Stranded [AWG]			
耐电压	Withstanding Voltage	1500V/1min		
IEC 技术参数		IEC 60947-7-4		
IEC Technical Data				
过电压类别	Overvoltage Category	III	III	II
污染等级	Contamination Class	3	2	2
额定电压	Rated Voltage [V]	250	400	630
额定电流	Rated Current [A]	24	24	24
额定冲击电压	Impulse withstand voltage [KV]	6.0	6.0	6.0
导线截面积	Conductor cross section	0.5-2.5		
硬质/柔性导线	Solid/ flexible [mm ²]			
一般参数 Other Data				
间距 Pitch / 极数 Poles	[mm] / [P]	7.5 / 02~24		
剥线长度	Stripping Length [mm]	5~6		
螺丝 Screw/扭矩 Torque(Max)	[N.m]	M3/0.5		
工作温度	Operating temperature [°C]	-40~105		
焊锡温度	Soldering temperature	260°C/5S		

DES.	CY	DATE	23.11.28	UNITS	mm	THIRD ANGLE PROJECTION	
CHK.	YangHJ	DATE	23.11.28	SIZE	A4	TYPE: CUSTOMER DRAWING	SHEET 1 of 1
APP.	JASON	DATE	23.11.28	SCALE	3:1	DRAWING TYPE: SP-03	REV V0
 慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD						PART NO.: WJ370-7.5-XXP-1Y-00A	