




Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非给予明确授权, 否则禁止转让、复制、利用、交流本文件的内容。侵犯者将承担赔偿责任。本公司保留对涉及发明、实用新型和外观专利的所有权利。



5		6			
REVISION RECORD					
REV.	ESCRIPTION		ECN No.	APPROVED	DATE
V0	新发行			WangP	24.01.17
9.50 1 0.30 3 2	UL/CUL 技术 参数				
	UL/CUL Technical Data				
	等 级	Use Group	B	C	D
	额定电压	Rated Voltage [V]	300	/	300
	额定电流	Rated Current [A]	20	/	10
	接线范围	Wire Range	30-12		
	单/多芯线	Solid/Stranded [AWG]			
	耐电压	Withstanding Voltage	1600V/1Min		
	IEC 技术参数				
	IEC Technical Data				
	过电压类别	Overvoltage Category	III	III	II
	污染等级	Contamination Class	3	2	2
	额定电压	Rated Voltage [V]	250	400	630
	额定电流	Rated Current [A]	24	24	24
	额定冲击电压	Impulse withstand voltage [KV]	4.0	4.0	4.0
	导线截面积	Conductor cross section	0.2-2.5		
	硬质/柔性导线	Solid/ flexible [mm²]			
	一般参数 Other Data				
间距	Pitch [mm]	5.0			
极数	Poles [P]	02-24			
剥线长度	Stripping Length [mm]	6~7			
螺丝	Screw	M3			
扭矩	Torque(Max) [N.m]	0.5			
工作温度	Operating temperature [°C]	-40~105			

WangP	DATE	24.01.17	UNITS	mm	THIRD ANGLE PROJECTION		
YangHJ	DATE	24.01.17	SIZE	A4	TYPE: CUSTOMER DRAWING	SHEET 1 of 1	
JASON	DATE	24.01.17	SCALE	3:1	DRAWING TYPE: SP-03	REV	V0
 慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD					PART NO.:		
					WJ123-5.0-XXP-1Y-00A		

General Tolerances								— ▯ ⊥		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60