





Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非给予明确授权,否则禁止转让、复制、利用、交还本文件内容。侵犯者将承担法律责任。本公司保留对涉及发明、实用新型和外观设计的所有权利。



P.C.B. LAYOUT



General Tolerances										
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 10	over 10 to 100	over 100 to 100	
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60



4	Header pin	Copper Alloy	Sn Plated
3	Screw	Steel	M3/Zn Plated
2	Cage	Copper Alloy	M3/Ni Plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

5

6

REVISION RECORD					
REV.	DESCRIPTION		ECN No.	APPROVED	DATE
V0	新发行			CY	23.11.28
UL/CUL 技术参数 UL/CUL Technical Data					
等 级	Use Group		B	C	D
额定电压	Rated Voltage	[V]	300	150	300
额定电流	Rated Current	[A]	20	20	10
接线范围	Wire Range		26-12		
单/多芯线	Solid/Stranded	[AWG]			
耐电压	Withstanding Voltage		1600V/1Min		
IEC 技术参数 IEC Technical Data					
过电压类别	Overvoltage Category		III	III	II
污染等级	Contamination Class		3	2	2
额定电压	Rated Voltage	[V]	450	630	1000
额定电流	Rated Current	[A]	24	24	24
额定冲击电压	Impulse withstand voltage	[KV]	6.0	6.0	6.0
导线截面积	Conductor cross section		0.5-2.5		
硬质/柔性导线	Solid/ flexible	[mm²]			
一般参数 Other Data					
间距 Pitch /极数 Poles	[mm] / [P]		7.62 / 02~24		
剥线长度	Stripping Length	[mm]	6~7		
螺丝 Screw/扭矩 Torque(Max)	[N.m]		M3/0.5		
工作温度	Operating temperature	[°C]	-40~105		
焊锡温度	Soldering temperature		260°C/5S		

DES.	CY	DATE	23.11.28	UNITS	mm	THIRD ANGLE PROJECTION		
CHK.	YangHJ	DATE	23.11.28	SIZE	A4	TYPE: CUSTOMER DRAWING		SHEET 1 of 1
APP.	JASON	DATE	23.11.28	SCALE	2.5:1	DRAWING TYPE: SP-03		REV V0
慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD						PART NO.: WJ129-7.62-XXP-1Y-00A		