




Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非给予明确授权，否则禁止转让、复制、利用、交流本文件的内容。侵犯者将负赔偿责任。本公司保留对涉及发明、实用新型和外观设计的所有权利。



General Tolerances								— ▯ ⊥		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60



4	Screw	Steel	M3/Zn Plated	DES.	WangP	DATE	23.12.01	UNITS	mm	THIRD ANGLE PROJECTION			
3	Cage	Copper Alloy	M3/Ni Plated	CHK.	YangHJ	DATE	23.12.01	SIZE	A4	TYPE: CUSTOMER DRAWING		SHEET 1 of 1	
2	Header Pin	Copper Alloy	Sn Plated	APP.	JASON	DATE	23.12.01	SCALE	2.5:1	DRAWING TYPE: SP-03		REV	V0
1	Housing	PA66	UL94V-0	 慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD						PART NO.: WJ129-5.0-XXP-1Y-00A			
ITEM	NAME OF PART	MATERIAL	NOTES										

5					6						
REVISION RECORD											
REV.		ESCRIPTION			ECN No.		APPROVED		DATE		
V0		新发行					WangP		23.12.01		
		UL/CUL 技术参数									
		UL/CUL Technical Data									
		等 级		Use Group		B	C	D			
		额定电压		Rated Voltage		[V]	300	-	300		
		额定电流		Rated Current		[A]	20	-	10		
		接线范围		Wire Range		26-12					
		单/多芯线		Solid/Stranded							[AWG]
		耐电压		Withstanding Voltage		1600V/1Min					
		IEC 技术参数									
		IEC Technical Data									
		过电压类别		Overvoltage Category		III	III	II			
		污染等级		Contamination Class		3	2	2			
		额定电压		Rated Voltage		[V]	250	400	630		
		额定电流		Rated Current		[A]	24	24	24		
		额定冲击电压		Impulse withstand voltage		[KV]	4.0	4.0	4.0		
		导线截面积		Conductor cross section		0.5-2.5					
		硬质/柔性导线		Solid/ flexible							[mm²]
		一般参数 Other Data									
		间距		Pitch /极数		Poles		[mm] / [P]		5.0 / 02~24	
		剥线长度		Stripping Length		[mm]		6~7			
螺丝		Screw/扭矩		Torque(Max)		[N.m] M3/0.5					
工作温度		Operating temperature		[°C]		-40~105					
焊锡温度		Soldering temperature		260°C/5S							