





Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非给予明确授权, 否则禁止转让、复制、利用、交流本文件的内容。侵犯者将承担赔偿责任。本公司保留对专利及发明、实用新型和外观设计的所有权利。



General Tolerances								— ▯ ⊥		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60



REVISION RECORD													
REV.		ESCRIPTION				ECN No.		APPROVED		DATE			
V0		新发行						CY		23.11.21			
3 1 2		UL/CUL 技术参数											
		UL/CUL Technical Data											
		等 级		Use Group		B		C		D			
		额定电压		Rated Voltage		[V]		300		-		300	
		额定电流		Rated Current		[A]		16		-		10	
		接线范围		Wire Range		22-12							
		单/多芯线		Solid/Stranded								[AWG]	
		耐电压		Withstanding Voltage		1600V/1Min							
		IEC 技术参数											
		IEC Technical Data											
		过电压类别		Overvoltage Category		III		III		II			
		污染等级		Contamination Class		3		2		2			
		额定电压		Rated Voltage		[V]		250		400		630	
		额定电流		Rated Current		[A]		20		20		20	
		额定冲击电压		Impulse withstand voltage		[KV]		4.0		4.0		4.0	
		导线截面积		Conductor cross section		0.5-2.5							
		硬质/柔性导线		Solid/ flexible								[mm²]	
		一般参数				Other Data							
间距		Pitch /极数		Poles		[mm] / [P]		5.0 / 02~24					
剥线长度		Stripping Length		[mm]		6~7							
螺丝		Screw/ 扭矩		Torque(Max)		[N.m]		M2.5/0.4					
工作温度		Operating temperature		[°C]		-40~105							
焊锡温度		Soldering temperature		260°C/5S									
		Header pin				Copper Alloy				Sn Plated			
		Screw				Steel				M2.5/Zn Plated			
		Cage				Copper Alloy				M2.5/Ni Plated			
		Housing				PA66				UL94V-0			
		NAME OF PART				MATERIAL				NOTES			
CY		DATE	23.11.21	UNITS	mm	THIRD ANGLE PROJECTION							
YangHJ		DATE	23.11.21	SIZE	A4	TYPE: CUSTOMER DRAWING				SHEET 1 of 1			
JASON		DATE	23.11.21	SCALE	4:1	DRAWING TYPE: SP-03				REV V0			
					慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD								
					PART NO.: WJ128E-5.0-XXP-1Y-00A								