


Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非给予明确授权, 否则禁止转让、复制、利用、交流本文件的内容。侵犯者将承担赔偿责任。 侵犯者将承担赔偿责任。 侵犯者将承担赔偿责任。



General Tolerances								— ▯ ⊥		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

4	Screw	Steel	Ni Plated	DES.	WangP	DATE	24.03.13	UNITS	mm	THIRD ANGLE PROJECTION			
3	Cage	Copper Alloy	Ni Plated	CHK.	YangHJ	DATE	24.03.13	SIZE	A4	TYPE: CUSTOMER DRAWING		SHEET 1 of 1	
2	Header Pin	Copper Alloy	Sn Plated	APP.	Jason	DATE	24.03.13	SCALE	2:1	DRAWING TYPE: SP-03		REV	V0
1	Housing	PA66(G25)	UL94V-0	 慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD						PART NO.:			
ITEM	NAME OF PART	MATERIAL	NOTES							WJ1010-10.0-XXP-1Y-01A			

REVISION RECORD					
REV.	DESCRIPTION		ECN No.	APPROVED	DATE
V0	新发行			WangP	24.03.13

UL/CUL 技术参数					
UL/CUL Technical Data					
等 级	Use Group		B	C	D
额定电压	Rated Voltage	[V]	300	-	300
额定电流	Rated Current	[A]	30	-	10
接线范围	Wire Range		26-12		
单/多芯线	Solid/Stranded	[AWG]			
耐电压	Withstanding Voltage		1600V/1Min		
IEC 技术参数					
IEC Technical Data					
过电压类别	Overvoltage Category		III	III	II
污染等级	Contamination Class		3	2	2
额定电压	Rated Voltage	[V]	250	400	630
额定电流	Rated Current	[A]	32	32	32
额定冲击电压	Impulse withstand voltage	[KV]	6	6	6
导线截面积	Conductor cross section		0.5-4.0		
硬质/柔性导线	Solid/ flexible	[mm²]			
一般参数 Other Data					
间距 Pitch /极数 Poles	[mm] / [P]		10.0 / 1~24		
剥线长度 Stripping Length	[mm]		4.5-5		
螺丝 Screw/ 扭矩 Torque(Max)	[N.m]		M4/1.2		
工作温度 Operating temperature	[°C]		-40~105		
焊锡温度 Soldering temperature			260°C/5S		