





Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非给予明确授权, 否则禁止转让、复制、利用、交流本文件的内容。侵犯者将承担赔偿责任。 本公司保留对涉及发明、实用新型和外观设计的所有权利。



5										6											
REVISION RECORD																					
REV.		ESCRIPTION								ECN No.		APPROVED				DATE					
V0		新发行										WangP				23.11.30					
8.50		UL/CUL 技术参数								cUL[®]us											
		UL/CUL Technical Data																			
		等 级		Use Group						B		C		D							
		额定电压		Rated Voltage [V]						150		-		-							
		额定电流		Rated Current [A]						7		-		-							
		接线范围		Wire Range						26-18											
		单/多芯线		Solid/Stranded [AWG]																	
		耐电压		Withstanding Voltage						1300V/1Min											
		IEC 技术参数								IEC60947-7-4											
		IEC Technical Data																			
		过电压类别		Overvoltage Category						III		III		II							
		污染等级		Contamination Class						3		2		2							
		额定电压		Rated Voltage [V]						63		130		320							
		额定电流		Rated Current [A]						8		8		8							
		额定冲击电压		Impulse withstand voltage [KV]						1.5		1.5		2.5							
		导线截面积		Conductor cross section						0.5-1.0											
		硬质/柔性导线		Solid/ flexible [mm ²]																	
		一般参数								Other Data											
		间距		Pitch / 极数		Poles		[mm] / [P]		2.54 / 02~24											
		剥线长度		Stripping Length [mm]								4~5									
螺丝		Screw/ 扭矩		Torque(Max)		[N.m]		M1.6/0.1													
工作温度		Operating temperature [°C]								-40~105											
焊锡温度		Soldering temperature								260°C/5S											

WangP	DATE	23.11.30	UNITS	mm	THIRD ANGLE PROJECTION					
YangHJ	DATE	23.11.30	SIZE	A4	TYPE: CUSTOMER DRAWING				SHEET 1 of 1	
JASON	DATE	23.11.30	SCALE	3.5:1	DRAWING TYPE: SP-03				REV	V0
 慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD					PART NO.:					
					WJEK254-2.54-XXP-1Y-00A					

General Tolerances								— ▯ ⊥		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60