



Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations.

除给予明确授权, 否则禁止转让、复制、利用、或文本文件的内容。使用者将承担赔偿责任。本公司保留对发明、实用新型和外观设计的所有权利。



General Tolerances								—		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
V0	新发行		YuCZ	23.11.02

UL/CUL	技术参数			
UL/CUL	Technical Data			
等级	Use Group	B	C	D
额定电压	Rated Voltage [V]	150	50	-
额定电流	Rated Current [A]	7	7	-
接线范围 单/多芯线	Wire Range Solid/Stranded [AWG]	28-18		
耐电压	Withstanding Voltage	1300V/1Min		

IEC 技术参数		IEC61984		
IEC Technical Data				
过电压类别	Overtoltage Category	III	III	II
污染等级	Contamination Class	3	2	2
额定电压	Rated Voltage [V]	80	160	200
额定电流	Rated Current [A]	10	10	10
额定冲击电压				
Impulse withstand voltage	[KV]	2.5	2.5	2.5

导线截面积	Conductor cross section	0.2-1.0
硬质/柔性导线	Solid/flexible [mm ²]	
一般参数 Other Data		
间距 Pitch / 极数 Poles	[mm] / [P]	3.5 / 2*02~2*24
剥线长度 Stripping Length	[mm]	7-8
工作温度 Operating temperature	[°C]	-40~105

符合RoHS环保要求			
5	Screw	Steel	M2/Zn plated
4	Clamp	Copper Alloy	Sn Plated
3	Spring	Stainless steel	
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

DES.	YuCZ	DATE	23.11.02	UNITS	mm	THIRD ANGLE PROJECTION		
CHK.	YangHJ	DATE	23.11.02	SIZE	A4	TYPE: CUSTOMER DRAWING	SHEET 1 of 1	
APP.	JASON	DATE	23.11.02	SCALE	2.5:1	DRAWING TYPE: SP-03	REV	VO

 慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD	PART NO.: WJ15DEGKSHM-3.5-2*XXP-1Y-00A
--	---