



General Tolerances											
variable range	to	over 6	over 10	over 30	over 60	over 100	over 160	to	over 10	over 100	over 100
		to 10	to 30	to 60	to 100	to 160	to 10	to 100	to 100	to 100	to 100
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60	

REVISION RECORD					
REV.	DESCRIPTION		ECN No.	APPROVED	DATE
0	新发行			YaoFei	24.01.18
UL/CUL	技术参数				
UL/CUL	Technical Data				
等级	Use Group	B	C	D	
额定电压	Rated Voltage [V]	300	-	-	
额定电流	Rated Current [A]	8	-	-	
接线范围	Wire Range				
单/多芯线	Solid/Stranded [AWG]				
耐电压	Withstanding Voltage				1600V/1Min
IEC 技术参数					IEC61984
IEC Technical Data					
过电压类别	Overvoltage Category	III	III	II	
污染等级	Contamination Class	3	2	2	
额定电压	Rated Voltage [V]	160	160	250	
额定电流	Rated Current [A]	8	8	8	
额定冲击电压	Impulse withstand voltage [KV]	2.5	2.5	2.5	
导线截面积	Conductor cross section				
硬质/柔性导线	Solid/ flexible [mm ²]				
一般参数	Other Data				
间距	Pitch / 极数 Poles [mm] / [P]				3.5 / 2*02~2*24
工作温度	Operating temperature [°C]				-40~+130
焊锡温度	Soldering temperature				285°C/10S
引针尺寸	Pin Dimensions [mm]				0.8*0.8
PCB板孔径	PCB Hole Diameter [mm]				Ø1.4
符合RoHS环保要求					

DES.	YaoFei	DATE	24.01.18	UNITS	mm	THIRD ANGLE PROJECTION	
CHK.	YangHJ	DATE	24.01.18	SIZE	A4	TYPE: CUSTOMER DRAWING	SHEET 1 of 1
APP.	JASON	DATE	24.01.18	SCALE	2:1	DRAWING TYPE: SP-03	REV 0
	慈溪市万捷电子有限公司		PART NO.:		WJ15EDGVHB-THT-3.5-2*XXP-1Y-00A		