

[illegible]

UL/CUL 技术参数				
UL/CUL Technical Data				
等 级	Use Group	B	C	D
额定电压	Rated Voltage [V]	150	/	/
额定电流	Rated Current [A]	5	/	/
接线范围	Wire Range	30-20		
单/多芯线	Solid/Stranded [AWG]			
耐电压	Withstanding Voltage	1300V/1Min		
IEC 技术参数		IEC61984		
IEC Technical Data				
过电压类别	Overvoltage Category	III	III	II
污染等级	Contamination Class	3	2	2
额定电压	Rated Voltage [V]	160	160	320
额定电流	Rated Current [A]	6	6	6
额定冲击电压	Impulse withstand voltage [KV]	2.5	2.5	2.5
导线截面积				
硬质/柔性导线	Solid/ flexible [mm²]	0.2-0.5		
一般参数 Other Data				
间距 Pitch / 极数 Poles	[mm] / [P]	2.54 / 2*02-2*24		
剥线长度	Stripping Length [mm]	7-8		
工作温度	Operating temperature [°C]	-40~105		
符合RoHS环保要求				
UNITS	mm	THIRD ANGLE PROJECTION		
SIZE	A4	TYPE: CUSTOMER DRAWING		SHEET 1 of 1
SCALE	2.5:1	DRAWING TYPE: SP-03		REV V0
子有限公司 TRONIC CO., LTD		PART NO.: WJ15EDGKNHBM-2.54-2*XP-1Y-00A		