




Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除注册给予明确授权，否则禁止转让、复制、利用、交流本文件的内容。侵犯者将承担法律责任。本公司保留对涉及发明、实用新型和外观设计的所有权利。



REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
V0	新发行		YuCZ	23.10.25

UL/CUL 技术 参数					
UL/CUL Technical Data					
等级	Use Group	B	C	D	
额定电压	Rated Voltage	[V]	150	—	—
额定电流	Rated Current	[A]	7	—	—
接线范围	Wire Range	/			
单/多芯线	Solid/Stranded				[AWG]
耐电压	Withstanding Voltage	1300V/1Min			
IEC 技术参数		IEC 61984			
IEC Technical Data					
过电压类别	Overvoltage Category	III	III	II	
污染等级	Contamination Class	3	2	2	
额定电压	Rated Voltage	[V]	80	125	250
额定电流	Rated Current	[A]	10	10	10
额定冲击电压	Impulse withstand voltage	[KV]	2.5	2.5	2.5
导线截面积	Conductor cross section	/			
硬质/柔性导线	Solid/ flexible				[mm²]
一般参数 Other Data					
间距	Pitch	[mm]	3.5		
极数	Poles	[P]	2*02-2*24		
工作温度	Operating temperature	[°C]	-40~105		
符合RoHS环保要求					
4	NUT	Copper Alloy	M2		
3	Pin 2	Copper Alloy	Sn Plated		
2	Pin 1	Copper Alloy	Sn Plated		
1	Housing	PA66(G25)	UL94V-0		
ITEM	NAME OF PART	MATERIAL	NOTES		

General Tolerances									
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 10	over 10 to 100	over 100 to 600
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30

DES.	YuCZ	DATE	23.10.25	UNITS	mm	THIRD ANGLE PROJECTION	
CHK.	YangHJ	DATE	23.10.25	SIZE	A4	TYPE: CUSTOMER DRAWING	SHEET 1 of 1
APP.	JASON	DATE	23.10.25	SCALE	3:1	DRAWING TYPE: SP-03	REV V0
慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD						PART NO.: WJ15EDGRHSM-3.5-2*XXP-1Y-00A	