


Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非给予明确授权，否则禁止转让、复制、利用、交流本文件的内容。侵犯者将承担赔偿责任。本公司保留对涉及发明、实用新型和外观专利的所有权利。



General Tolerances								— ▯ ⊥		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

6	Screw 2	Steel	M2.5/Zn Plated
5	Clamp	Copper Alloy	Ni Plated
4	Screw 1	Steel	M2/Zn Plated
3	Cage	Copper Alloy	M2/Ni Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

DES.	YaoFei	DATE	23.10.12	UNITS	mm	THIRD ANGLE PROJECTION	
CHK.	YangHJ	DATE	23.10.12	SIZE	A4	TYPE: CUSTOMER DRAWING	
APP.	JASON	DATE	23.10.12	SCALE	3:1	DRAWING TYPE: SP-03	
PART NO.: WJ15EDGKM-3.5-XXP-1Y-00A						REV	0

REVISION RECORD					
REV.	DESCRIPTION		ECN No.	APPROVED	DATE
0	新发行			YaoFei	23.10.12

UL/CUL 技术参数		UL/CUL Technical Data					
等级	Use Group			B	C		D
额定电压	Rated Voltage	[V]	300	-	300		
额定电流	Rated Current	[A]	8	-	8		
接线范围	Wire Range				28-16		
单/多芯线	Solid/Stranded	[AWG]					
耐电压	Withstanding Voltage						1600V/1Min

IEC 技术参数		IEC Technical Data				
过电压类别	Overvoltage Category	III	III	II		
污染等级	Contamination Class	3	2	2		
额定电压	Rated Voltage	[V]	160	160	250	
额定电流	Rated Current	[A]	7	7	7	
额定冲击电压	Impulse withstand voltage	[KV]	2.5	2.5	2.5	
导线截面积	Conductor cross section	0.5-1.5				
硬质/柔性导线	Solid/ flexible	[mm²]				

一般参数		Other Data			
间距	Pitch / 极数	Poles	[mm] / [P]	3.5 / 02~24	
剥线长度	Stripping Length	[mm]		6~7	
螺丝	Screw/ 扭矩	Torque(Max)	[N.m]	M2/0.2	
工作温度	Operating temperature	[°C]		-40~105	

6.70

符合RoHS环保要求					
------------	--	--	--	--	--