

123456

REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
V0	新发行		YuCZ	23.11.27

Top view dimensions: 3.50 , $3.50(XX-1)$, $3.50XX+0.7$, $3.50(XX+1)$, 7.70 .

Side view dimensions: $24.40(REF)$, 22.50 , 7.00 , 7.20 .

Front view dimensions: 7.70 .

General Tolerances										—	□	⊥
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 10	over 10 to 100	over 100 to			
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60		

UL/CUL 技术参数		UL/CUL Technical Data		
等级	Use Group	B	C	D
额定电压	Rated Voltage [V]	300	-	300
额定电流	Rated Current [A]	8	-	8
接线范围	Wire Range	24-16		
单/多芯线	Solid/Stranded [AWG]	24-16		
耐电压	Withstanding Voltage	1600V/1Min		

IEC 技术参数		IEC Technical Data		
过电压类别	Overvoltage Category	III	III	II
污染等级	Contamination Class	3	2	2
额定电压	Rated Voltage [V]	160	160	320
额定电流	Rated Current [A]	8	8	8
额定冲击电压	Impulse withstand voltage [KV]	2.5	2.5	2.5
导线截面积	Conductor cross section	0.5-1.5		
硬质/柔性导线	Solid/flexible [mm²]	0.5-1.5		

一般参数 Other Data			
间距	Pitch / 极数 Poles [mm] / [P]	3.5 / 02~24	
剥线长度	Stripping Length [mm]	9-10	
工作温度	Operating temperature [°C]	-40~105	

符合RoHS环保要求			
ITEM	NAME OF PART	MATERIAL	NOTES
5	Button	POM	UL94-HB
4	Clamp	Copper Alloy	Sn Plated
3	Spring	Stainless steel	
2	Housing 2	PA66	UL94V-0
1	Housing 1	PA66	UL94V-0

DES.	YuCZ	DATE	23.11.27	UNITS	mm	THIRD ANGLE PROJECTION	⊗
CHK.	YangHJ	DATE	23.11.27	SIZE	A4	TYPE: CUSTOMER DRAWING	SHEET 1 of 1
APP.	JASON	DATE	23.11.27	SCALE	2:1	DRAWING TYPE: SP-03	REV V0

慈溪市万捷电子有限公司
CIXI WANJIE ELECTRONIC CO., LTD

PART NO.:
WJ15EDGKNRT-3.5-XXP-1Y-00A

FOR-0371 Rev.1.0

D